

SPORE BLACK

Powder Free Static Dissipative Finger Cots

Code: F6R-PF-size



Product Specification :

| | | | | |
|------------------------|------------------|-----|-----|------|
| Size | S15 | M18 | L21 | XL24 |
| Internal Diameter (mm) | 15 | 18 | 21 | 24 |
| Thickness (mm) | 0.1 | | | |
| Length (mm) | 63 | | | |
| Material | 100% Sheer Latex | | | |
| Style | Rolled | | | |
| Type | Powder Free | | | |
| Packing | 720 / pack | | | |
| Master Case | 40 pks | | | |

Features & Benefits :

- Consistent conductive level guaranteed
- For use with Class 1 Category A (<100v)
- Cots meet ASTM 3772 requirements for quality consistency.
- Chlorine level is monitored and controlled for consistent quality of powder-free cots to prevent excess chlorides.

Surface Resistivity & Physical Properties :

- Avg surface resistivity is 10(6)~10(8) ohms/sq. reference ASTM D257
- Tensile Strength : Min 30 Mpa
- Elongation : Min 700%

Static Decay Test :

- 5000 to 0 volts in 0.01 second. The cots meet MIL-STD-81705B

Recommended Storage Conditions :

- Store indoor cool and dry place below 25c
- Avoid heat, direct sunlight and chemical damages

Shelf Life :

- Approx 9 months